

Sub C11)

2

3

4

5

6

7

8

9

1

2

2

1

2

1

2

1 ~~6. The method of claim 3 wherein said water-soluble polymer comprises~~
 2 starch.

SubC2}

1 ~~7. The method of claim 1 wherein~~
 2 said precursor brine comprises a salt selected from the group consisting of
 3 calcium salts, magnesium salts, sodium salts, potassium salts, aluminum
 4 salts, lithium salts, and combinations thereof; and
 5 said first salt content comprises a density of between about 9-14 pounds per
 6 gallon.

1 ~~8. The method of claim 2 wherein~~
 2 said precursor brine comprises a salt selected from the group consisting of
 3 calcium salts, magnesium salts, sodium salts, potassium salts, aluminum
 4 salts, lithium salts, and combinations thereof; and
 5 said first salt content comprises a density of between about 9-14 pounds per
 6 gallon.

SubC3}

1 ~~9. The method of claim 3 wherein~~
 2 said precursor brine comprises a salt selected from the group consisting of
 3 calcium salts, magnesium salts, sodium salts, potassium salts, aluminum
 4 salts, lithium salts, and combinations thereof; and

08869109-060497

SubC37
CPT

said first salt content comprises a density of between about 9-14 pounds per
gallon.

6

1

2

3

4

5

6

10. The method of claim 6 wherein
said precursor brine comprises a salt selected from the group consisting of
calcium salts, magnesium salts, sodium salts, potassium salts, aluminum
salts, lithium salts, and combinations thereof; and
said first salt content comprises a density of between about 9-14 pounds per
gallon.

1

2

3

4

5

11. The method of claim 1 wherein
said precursor brine comprises a salt selected from the group consisting of
calcium chloride, calcium bromide, and combinations thereof; and
said first salt content comprises a density of between about 9-14 pounds per
gallon.

1

2

3

4

5

6

12. The method of claim 2 wherein
said precursor brine comprises a salt selected from the group consisting of
calcium chloride, calcium bromide, and combinations thereof; and
said first salt content comprises a density of between about 9-14 pounds per
gallon.

08869109 060497

7 13. The method of claim 3 wherein

8 said precursor brine comprises a salt selected from the group consisting of

9 calcium chloride, calcium bromide, and combinations thereof; and

10 said first salt content comprises a density of between about 9-14 pounds per

11 gallon.

12 14 15. A method for producing a precursor polymer dispersion for addition to

1 a final brine for use in drilling and completion operations comprising:

3 providing a precursor brine having a first salt content comprising a density of

4 between about 9-14 pounds per gallon of a salt selected from the group

5 consisting of calcium chloride, calcium bromide, and combinations

6 thereof; and

7 mixing between about 1-2 lb/gal of a water-soluble polymer with said precursor

8 brine under conditions sufficient to produce a precursor polymer

9 dispersion effective at a sufficient concentration in a final brine having a

10 second salt content to improve a property of said final brine selected

11 from the group consisting of rheology, fluid loss control, and a

12 combination thereof.

1 12 16. A method for treating a high density brine for use in drilling and

2 completion operations comprising:

3 providing a precursor brine having a first salt content;

264090-60769880

Sub 47
file
126

4
Sub 44
cond 5

6 mixing a water-soluble polymer with said precursor brine at a sufficient
7 concentration and under conditions sufficient to produce a precursor
8 polymer dispersion effective at a sufficient concentration in a final brine
9 having a second salt content to improve a property of said final brine
10 selected from the group consisting of rheology, fluid loss control, and a
11 combination thereof; and
12 mixing said sufficient concentration of said precursor polymer dispersion with
13 said final brine.

1 16. The method of claim 16 wherein said sufficient concentration is
2 between about 0.5-4 lb of said water-soluble polymer per gallon of said precursor
3 brine.

1 17. The method of claim 16 wherein said sufficient concentration is
2 between about 1-2 lb of said water-soluble polymer per gallon of said precursor brine.
3

1 18. The method of claim 15 wherein said water-soluble polymer comprises
2 starch.

1 19. The method of claim 16 wherein said water-soluble polymer comprises
2 starch.

0869109 06049
264090 60769880

~~20~~
~~21~~

~~22.~~

~~22~~
~~23.~~

~~25~~
~~24.~~

24
25. The method of claim 18 wherein
said precursor brine comprises a salt selected from the group consisting of
calcium chloride, calcium bromide, and combinations thereof; and
said first salt content comprises a density of between about 9-14 pounds per
gallon.

25
26. The method of claim 21 wherein
said precursor brine comprises a salt selected from the group consisting of
calcium chloride, calcium bromide, and combinations thereof; and
said first salt content comprises a density of between about 9-14 pounds per
gallon.

26
27. A precursor polymer dispersion for addition to a final brine for use in
drilling and completion operations comprising:
a first salt content;
a water-soluble polymer in an amount effective at a sufficient concentration in a
final brine having a second salt content to improve a property of said
final brine selected from the group consisting of rheology, fluid loss
control, and a combination thereof.

Add
B1

Add C17

08869109 "06697"